

# ACCESSORIES

ROQ Foil	3550
drawing width (mm / inch)	350x500 / 17"x24"
compr. air consumption at 7 bar (l/min. /cfm)	95 / 3.4
power supply (VAC)	230V+N, 2x230V
maximum temperature (°C)	200
max. consumption (kVA)	2.5
total length (mm / feet)	1450 / 4.75'
total height (mm / feet)	1400 / 4.6'
total width (mm / feet)	760 / 2.5'

ROQ Iron	M	XL
iron (mm / inch)	400 / 16"	600 / 24"
max. consumption (kVA)	2.2	3
course (mm / inch)	550 / 21"	850 / 33"
screen (mm / inch)	900x563 / 36"x22"	1200x763 / 47"x30"
temperature (°C)	200	200
power supply (VAC)	230V+N, 2x230V	

ROQ Flock	4060	4595	6085
flock type (recommended)	polyamide		
flock's length (mm) - thickness (inch)	0.5 - 1.5 (3.3 dtex)		
high tension power supply (kV)	10-80		
flocking area (mm / inch)	400x600 / 16"x24"	450x950 / 18"x37"	600x850 / 24"x33"
maximum frame size (mm / inch)	604x988 / 24"x39"	654x1338 / 26"x53"	804x1238 / 32"x49"
rec. frame profile (mm / inch)	40x20 / 1.6"x0.8"	40x20 / 1.6"x0.8"	40x20 / 1.6"x0.8"
total length (mm / feet)	1300 / 4.25'	1350 / 5.4'	1550 / 5.1'
total height (mm / feet)	1230 / 4'	1230 / 4'	1230 / 4'
total width (mm / feet)	760 / 2.5'	810 / 2.6'	920 / 3'
power supply (VAC)	230V+N, 2x230V		
max. consumption (kVA)	0.2		

ROQ Storm	3550
length (mm / inch)	2200 / 86.6"
height (mm / inch)	2975 / 117"
width (mm / inch)	850 / 33.5"
suction max. width (mm / inch)	785 / 30.9"
max. length of the piece of aspiration (mm / inch)	900 / 35.4"
electrical consumption (kVA)	3
power supply (VAC)	230V+N, 2x230V



## ROQ Asp

- ROQ Asp is designed to vacuum excess flock after the flocking process.
- This accessory is mounted on a printhead and is fully compatible with the ROQ automatic screen printing machines
- Available in two widths: 620 mm/24" and 470 mm/18"

## ROQ Foil

- Compatible with ROQ You, Next, Eco, Oval Run, Oval Pro and Oval Evolution
- Fully automatic foil application
- No human intervention in the process
- Maximum production of 450 pieces per hour

## ROQ Iron

- Compatible with any ROQ automatic screen printing machine
- Powered using the machine power connections
- Temperature control
- Max temperature 200 °C
- Speed/pressure regulated by the printhead
- Press with 400 mm/15.7" and 600 mm/23.6" width

## ROQ Flock

- Compatible with ROQ You, Next, Eco, Oval Pro, Oval Run and Oval Evolution
- Closed system leading to minimum color contamination
- 80kV electrostatic generator
- Micro registration screen system with vernier scale
- Maximum production of 600 pieces per hour

## ROQ Storm

- ROQ Storm is an independent module created to vacuum/clean fabric, either from flock or other impurities the fabric might have
- Fabric pieces up to 787mm/27.56" wide and 900mm/35.43" long